

# TEKNISKA SPECIFIKATIONER



**PEUGEOT**  
MOTOCYCLES

FRAME	METROPOLIS 400	SPEEDFIGHT 4 2-STROKE	4-STROKE	STREETZONE 10"	12"	DJANGO HERITAGE & SPORT 2-STROKE	4-STROKE	DJANGO EVASION	KISBEE	KISBEE RS/BLACK EDITION
Tyres Front	110/70-13	130/60-13	130/60-13	120/90-10	120/70-12	120/70-12	120/70-12	120/70-12	110/70-12	110/70-12
Tyres Rear	140/70-14	130/60-13	130/60-13	130/90-10	120/70-12	130/60-12	130/60-12	130/60-12	110/70-12	110/70-12
Braking Front	Disc Ø 230mm	Radial Shuricane Ø 215mm	Radial Shuricane Ø 215mm	Disc Ø 190mm	Disc Ø 190mm	Disc Ø 200mm	Disc Ø 200mm	Disc Ø 200mm	Disc Ø 170mm	Shuricane Ø 170mm
Braking Rear	Disc Ø 240mm	Drum Ø 110mm	Drum Ø 190mm	Disc Ø 110mm	Disc Ø 110mm	Drum Ø 110mm	Drum Ø 110mm	Drum Ø 196mm	Drum Ø 110mm	Drum Ø 110mm
Suspension Front	Single front hydraulic shock absorber	Upside-down hydraulic telescopic fork	Upside-down hydraulic telescopic fork	Upside-down hydraulic telescopic fork	Upside-down hydraulic telescopic fork	Hydraulic telescopic fork	Hydraulic telescopic fork	Hydraulic telescopic fork	Hydraulic telescopic fork	Hydraulic telescopic fork
Suspension Rear	Dual rear adjustable hydraulic shock absorber	Hydraulic shock absorber	Hydraulic shock absorber	Hydraulic shock absorber	Hydraulic shock absorber	Hydraulic shock absorber 5 pos adjustable	Hydraulic shock absorber 5 pos adjustable	Hydraulic shock absorber 5 pos adjustable	Hydraulic shock absorber	Hydraulic shock absorber

## ENGINE

Engine type	4-stroke, 4 valves	2-stroke	4-stroke, 2 valves	2-stroke	2-stroke	2-stroke	4-stroke, 2 valves	4-stroke	4-stroke, 2 valves	4-stroke, 2 valves
Cubic capacity cm <sup>3</sup>	400	49.9	49.5	49.9	49.9	49.9	49.9	150	49.9	49.9
Cooling	Liquid	Air	Air	Air	Air	Air	Air	Air	Air	Air
Standard	Euro 4	Euro 4	Euro 4	Euro 4	Euro 4	Euro 2	Euro 2	Euro 4	Euro 4	Euro 4
Maximum power	27,4kW (37hp)	3,4kW (4,6hp)	2,8kW (3,6hp)	3,4kW (4,6hp)	3,4kW (4,6hp)	3,0kW (4,1hp)	2,8kW (3,8hp)	8,3kW	2,7kW (3,7hp)	2,7kW (3,7hp)
Maximum torque	38,1Nm at 5250 rpm	4,2Nm at 5800 rpm	3,73Nm at 6500 rpm	4,2Nm at 6500 rpm	4,2Nm at 6500 rpm	4,6Nm at 5800 rpm	3,6Nm at 6600 rpm	11,0Nm at 7000 rpm	3,6Nm at 7000 rpm	3,6Nm at 7000 rpm
Fuel supply	Injection	Injection	Carburettor autochoke	Injection	Injection	Carburettor autochoke	Carburettor autochoke	Injection	Carburettor autochoke	Carburettor autochoke

## DIMENSIONS

Unladen weight (kg)	256 kg	97 kg	100 kg	87 kg	87 kg	110 kg	110 kg	140 kg	85 kg	85 kg
Length	2160 mm	1895 mm	1895 mm	1864 mm	1864 mm	1925 mm	1925 mm	1925 mm	1854 mm	1854 mm
Width	745 mm	700 mm	700 mm	664 mm	664 mm	710 mm	710 mm	710 mm	664 mm	664 mm
Height	1445 mm	1150 mm	1150 mm	1166 mm	1166 mm	1190 mm	1190 mm	1190 mm	1156 mm	1156 mm
Wheelbase	1555 mm	1306 mm	1306 mm	1256 mm	1256 mm	1350 mm	1350 mm	1350 mm	1296 mm	1296 mm
Saddle height	780 mm	800 mm	800 mm	770 mm	770 mm	770 mm	770 mm	770 mm	760 mm	760 mm
Fuel tank	13,4 liter	8,0 liter	8,0 liter	6,5 liter	6,5 liter	8,5 liter	8,5 liter	8,5 liter	6,5 liter	6,5 liter

## STORAGE

Under-saddle storage compartment & Hatch	Power operated 1 full-face helmet + 1 half-face helmet with visor	1 full-face helmet	1 full-face helmet	1 full-face helmet	1 full-face helmet	1 visor-equipped, open-face jet helmet	1 visor-equipped, open-face jet helmet	1 visor-equipped, open-face jet helmet	1 full-face helmet	1 full-face helmet
--	---	--------------------	--------------------	--------------------	--------------------	--	--	--	--------------------	--------------------